

Glove SG A187



TOWA



Description	Seamless glove with nitrile foam coating
Material	Liner: Polyester (13 gauge), dual-colour Coating: nitrile foam, sandy
Application areas	Assembly, industry, construction, etc.
Product advantages	high-quality nitrile coating, thus very good mechanical properties (abrasion), oil-resistant palm in "MicroFinish™" (surface resembles suction cups), thus particular good grip touchscreen compatible very good dexterity and well-known TOWA-shape
Single packaging	headercard
Standards	KAT II, EN ISO 21420:2020, EN 388:2016+A1:2018

Certification:

Feature	Level	Range
Abrasion resistance	3	Min 0 / Max 4
Cut resistance (Coupe-Test)	1	Min 0 / Max 5
Tear resistance	2	Min 0 / Max 4
Puncture resistance	1	Min 0 / Max 4
Cut resistance (ISO 13997)	X	A-F (X=not tested)

Rating	Range (• - ●●●●)
Durability	●●●●
Dexterity	●●●●
Moisture protection	●●
Grease/Oil resistance	●●●●
Slip resistance	●●●●●
Breathability	●●●●

Logistical Data:

Item no.	Size	Barcode	MOQ	Packaging Unit	Pal
297666	7 / S	4018653265840	1 Pair	1/6/144	1.440
297667	8 / M	4018653265857	1 Pair	1/6/144	1.440
297668	9 / L	4018653265864	1 Pair	1/6/144	1.440
297669	10 / XL	4018653265871	1 Pair	1/6/144	1.440
297670	11 / XXL	4018653265888	1 Pair	1/6/144	1.440